

CODE NUMBER

3400026

DESCRIPTION

0.25 gpf, Matte White Finish, Fixture Connection Top Spud, Single Flush, TruFlush Concealed Manual Urinal Flushometer.

DETAILS

- Flush Volume: 0.25 gpf (0.9 Lpf)
- Finish: Matte White (MW)
- Valve: Piston
- Valve Body Material: Semi-red Brass
- Fixture Type: Urinal
- Fixture Connection: Top Spud

FEATURES

- High Efficiency flush volume for water conservation
- Corrosion-resistant, vandal resistant wall plate
- Piston color-coded by flush volume for easy identification
- Easy to push manual button is ADA compliant- less than 5 lbf/22N of force required to activate
- Flood prevention feature limits flow to a trickle in the wide open position
- Heavy duty brass valve body
- Safety collar locks activation assembly to prevent access of internal components without shutting off water
- Replaceable piston assembly, accessible through front wall plate
- Concealed shut off sleeve adjusts flow rate - accessible without removing button/bracket assembly
- 1-1/2" NPT (female) Inlet standard
- 1-1/2" NPSM Outlet standard
- Fixed Volume Piston with Filtered O-ring Bypass

VIDEOS

- TruFlush
- TruFlush Installation
- TruFlush Maintenance
- TruFlush Flush Line



COMPLIANCES & CERTIFICATIONS



(ADA Compliant, BREEAM Water Credit, Green Globes Water Credit)

RECOMMENDED SPECIFICATION

Valve shall be concealed with front access wall plate smaller than 7" x 7" and shall have integrated control stop. Valve shall be in compliance with ASTM Alloy Classification for Semi-Red Brass.

VALVE OPERATING PRESSURE (FLOWING)

15-80 PSI (103-552 kPa). Specific fixtures may require greater minimum flowing pressure - consult manufacturer requirements.

DOWNLOADS

- [TruFlush Manual Installation Instructions](#)
- [TruFlush Manual Installation Instructions \(Spanish\)](#)
- [TruFlush Repair and Maintenance Guide](#)
- [Additional Downloads](#)

NOTES

All information contained within this document subject to change without notice.

Looking for other variations of the TRF 196 product? [View the general spec sheet with all options.](#)

[Find a compatible urinal](#) for this flushometer.

[Find a compatible water closet](#) for this flushometer.

Sloan 10500 Seymour Ave, Franklin Park, IL 60131

Phone: 800.982.5839 • Fax: 800.447.8329 • sloan.com

ROUGH-IN

NOTE : Flush Connections shown in dotted lines not included.

