



ART.4315	
<i>Press Fitting-female for multilayers pipes</i>	
SPECIFICATION	
Series	4315
Thread ends	Pipe-Female: UNI ISO7/1
APPLICATION	
Assembly in rigid pipe system	
Nominal pressure: (referred to multilayer pipe) 0.5 bar Max for GAS 10 bar Max for WATER	
Temperature range: -15°C/+50°C for GAS 0°C/+80°C for WATER	
Use: WATER-GAS	

N°	Descrizione	Description	Materials	Q.ty
1	Raccordo	Fitting	CW617N	1
2	O-Ring	O-Ring	NBR70Sh *	2
3	Anello Isolante	Insulation Ring	Nylon	1
4	Bussola	Bush	AISI 304	1

* = NBR for WATER and GAS

Dimensions	Rp	D	L	CH
16 x 1/2"	1/2"	16x2	49	24
18 x 1/2"	1/2"	18x2	48	24
16 x 3/4"	3/4"	16x2	49	30
20 x 1/2"	1/2"	20x2	47	24
20 x 3/4"	3/4"	20x2	47	30
25 x 3/4"	3/4"	25x2,5	49	30
26 x 3/4"	3/4"	26x3	49	30
25 x 1"	1"	25x2,5	52	37,5
26 x 1"	1"	26x3	52	37,5
32 x 1"	1"	32x3	53	37,5

Denominazione particolare / Name Raccordo F/Pressare		Disegnato / Designed by Pedretti W.	Formato / Format A3	Grezzo / Forged Code -	Quote senza indicazione di tolleranza: MEDIA UNI-ISO 2768/1
Materiale / Material CW617N		Approvato / Approved by Borghetti R	Scala / Scale 2:1	Lavorato / Finished Code -	Rugosità Generale ^{3.2} / (^{0.7}) General Roughness
Tratt. Superficiale / Surface Treat. Tratt. Termico / Thermal Treat.		Data / Date 11/04/2012	Foglio / Tab. 1/1	Trattato / Treaty Code -	Valido per / Available for Consultazione
N° Disegno / Drawing Nr. 4315		Revisone / Revision -	Peso / Weight g	Misura / Size -	<p>BUGATTI VALVOSANITARIA</p> <p>UFFICIO TECNICO</p>