



- | | |
|--|--|
| LG89-7FEBG Finish(BG) <input type="checkbox"/> | LG89-8FEBG Finish(BG) <input type="checkbox"/> |
| LG89-7FEC Finish(C) <input type="checkbox"/> | LG89-8FEC Finish(C) <input type="checkbox"/> |
| R89-1FED Finish(D) <input type="checkbox"/> | LG89-7FED Finish(D) <input type="checkbox"/> |
| R89-1FEK Finish(K) <input type="checkbox"/> | LG89-8FEK Finish(K) <input type="checkbox"/> |
| R89-1FEC Finish(C) <input type="checkbox"/> | R89-1FEY Finish(Y) <input type="checkbox"/> |
| LG89-7FEY Finish(Y) <input type="checkbox"/> | LG89-8FEY Finish(Y) <input type="checkbox"/> |

R89-1FEBG Finish(BG)

R89-1FED Finish(D)

LG89-7FED Finish(D)

LG89-8FED Finish(D)

R89-1FEK Finish(K)

LG89-7FEK Finish(K)

LG89-8FEK Finish(K)

R89-1FEC Finish(C)

R89-1FEY Finish(Y)

LG89-7FEY Finish(Y)

LG89-8FEY Finish(Y)

Specifications

- SecurePfit™ Trim
- Trim Only, Valve Not Included

Features

- 1.8 GPM Flow Rate (Showerhead)
- SecurePfit™ with Anti Handle Wobble
- Raincan Showerhead
- Shower Only (7FE Only)
- Tub & Shower (8FE Only)
- Valve Trim Only (1FE Only)
- Brass Ball Joint
- Trim Only, Valve Not Included
- Requires OX8/JX8 Valve (Order Separately)
- Metal Shower Arm and Flange
- Quick Connect Tub Spout (8FE Only)
- Temperature Control Only
- Pforever Warranty®

Code Compliance

Pfister products are designed and manufactured in compliance with the following standards and codes:

- IAPMO Certified
- CSA B125 Certified
- ASME A112.18.1
- Cal Green Compliant
- CEC Compliant
- ADA Compliant-ANSI A117.1 (Lever handles only)
- EPA WaterSense Certification 1.8 gpm, 6.8 L/Min



Dimensions

