

615PV

15 Amp, 250 Volt, NEMA 6-15P, 2P, 3W, Plug, Straight Blade , Grounding - YELLOW



UPC Code : 078477842287

Country Of Origin : Mexico



Technical Information

Electrical Specifications

Amperage : 15 A

Current Interrupting : Certified for current interrupting at full rated current

Dielectric Voltage : Withstands 2000V per UL498

Grounding : Grounding

Pole : 2

Temperature Rise : Max 30C after 50 cycles OL at 150 percent rated current

Voltage : 250 VAC

Wire : 3

Environmental Specifications

Flammability : Rated V-2 per UL 94

Operating Temperature : -40°C to 60°C

Material Specifications

Assembly Screws : Steel, Zinc Plated

Blades/Contacts : Brass

Body Material : PVC

Color : Yellow

Mechanical Specifications

Cord Range : .245 - .655

Product ID : Ratings and NEMA I.D. permanently marked on device

Terminal Accom. : 18-12 AWG

Terminal ID : Brass-Hot, Green-Ground, Silver-Neutral

Product Features

Color : Yellow

Cord Range : .245 - .655

NEMA : 6-15P

Standards and Certifications

ANSI : C-73

CSA C22.2 No. 42 : File LR-406

NEMA : WD-6

NOM : 057

UL498 : File E13393

Warranty : 2-Year Limited



JOB NAME:	CATALOG NUMBERS:	
JOB NUMBER:		

Telephone: +1-800-323-8920 · FAX: +1-800-832-9538 · Tech Line (8:30AM-7:30PM E.S.T. Monday-Friday):
+1-800-824-3005

165 Hymus Boulevard, Pointe Claire, Quebec H9R 1E9 · Telephone: +1-800-469-7890 · FAX: +1-800-824-3005 · www.leviton.com/canada

Lago Tana 43, Mexico DF, Mexico CP 11290 · Tel.: (+52)55-5082-1040 · FAX: (+52)5386-1797 · www.leviton.com.mx

© 2018 Leviton Manufacturing Co., Inc. All Rights Reserved. Subject to change without notice.

If you would like to know where your local Leviton office is located please go to:
www.leviton.com/international/contacts/

