



UPC Code : 078477908846

Country Of Origin : Mexico

## 16262-OIG

Decora Plus Isolated Ground Duplex Receptacle Outlet, Heavy-Duty Industrial Specification Grade, Smooth Face, 15 Amp, 125 Volt, Back or Side Wire, NEMA 5-15R, 2-Pole, 3-Wire, Self-Grounding - Orange

### Technical Information

#### Product Features

**Color** : Orange

**Color / Feature** : Orange

**Device Type** : Decora Plus Duplex Receptacle

**Grade** : Heavy-Duty Industrial Specification Grade

**Horsepower Rating** : 1/2 HP

#### Warranty

**Amperage** : 15 A

**Dielectric Voltage** : Withstands 3000 V minimum

**Grounding** : Self-Grounding

**Pole** : 2

**Temperature Rise** : Max 30 °C after 250 cycles OL at 200 percent rated current

**Voltage** : 125 VAC

**Warranty** : 10-Year Limited

**Wire** : 3

#### Mechanical Specifications

**Flammability** : Rated V-0 per UL 94

**Operating Temperature** : -40°C to 75°C

**Product ID** : Ratings are permanently marked on device

**Shutter Mechanism** : Acetal

**Terminal Accom.** : #14 AWG - #10 AWG

**Terminal ID** : Brass - Hot, Green - Ground, Silver - Neutral

**Termination** : Back and Side Wire

**Wire Type** : Stranded or Solid

#### AC Horsepower Rating

**Body Material** : PBT Polyester Blend

**Face Material** : PBT Polyester Blend

**Ground Clips** : Brass

**Ground Contacts** : 0.030" Brass

**Grounding Screw** : #8 hex head, triple drive Brass

**Horsepower Rating** : 1/2 HP

**Line Contacts** : 0.030" Phosphor Bronze

**Mounting Screws** : Triple-Drive Plated Steel

**Strap Material** : Steel

**Terminal Clamps** : Brass

**Terminal Screws** : #8 Triple-Drive Brass

#### Electrical Specifications

**Dielectric Voltage** : Withstands 3000 V minimum

**Grounding** : Self-Grounding

**Pole** : 2

**Product ID** : Ratings are permanently marked on device

**Temperature Rise** : Max 30 °C after 250 cycles OL at 200 percent rated current

**Terminal Accom.** : #14 AWG - #10 AWG

**Terminal ID** : Brass - Hot, Green - Ground, Silver - Neutral

**Termination** : Back and Side Wire

**Voltage** : 125 VAC

**Wire** : 3

**Wire Type** : Stranded or Solid

#### Environmental Specifications

**Color / Feature** : Orange

**Flammability** : Rated V-0 per UL 94

**Grade** : Heavy-Duty Industrial Specification Grade

**Operating Temperature** : -40°C to 75°C

#### Material Specifications

**ANSI** : C-73

**Applicable Standards** : UL 498, Fed Spec W-C-596, CSA C22.2. No. 42

**Body Material** : PBT Polyester Blend

**Certification/Listing** : cULus, NOM-ANCE

**Face Material** : PBT Polyester Blend

**Ground Clips** : Brass

**Ground Contacts** : 0.030" Brass

**Grounding Screw** : #8 hex head, triple drive Brass

**Line Contacts** : 0.030" Phosphor Bronze

**Mounting Screws** : Triple-Drive Plated Steel

**RoHS** : RoHS Compliant

**Strap Material** : Steel

**Terminal Clamps** : Brass

**Terminal Screws** : #8 Triple-Drive Brass

#### Standards & Certifications

**ANSI** : C-73

**Applicable Standards** : UL 498, Fed Spec W-C-596, CSA C22.2. No. 42

**Certification/Listing** : cULus, NOM-ANCE

**RoHS** : RoHS Compliant

**Amperage : 15 A**

**Patents\***

MX321216

US8684771

MX324598

US8777674

\*This list is provided for patent marking purposes only. A good faith effort is made to maintain the accuracy and completeness of this list. No legal inference should be drawn from the omission of a patent from this list.

**SPECIFICATION SUBMITTAL**

<b>JOB NAME:</b> <input type="text"/>	<b>CATALOG NUMBERS:</b> <input type="text"/>	
<b>JOB NUMBER:</b> <input type="text"/>	<input type="text"/>	<input type="text"/>

**Leviton Manufacturing Co., Inc.**

201 North Service Road, Melville, NY 11747

Telephone: +1-800-323-8920 · FAX: +1-800-832-9538 · Tech Line (8:30AM-7:30PM E.S.T. Monday-Friday):

+1-800-824-3005

**Leviton Manufacturing of Canada, Ltd.**

165 Hymus Boulevard, Pointe Claire, Quebec H9R 1E9 · Telephone: +1-800-469-7890 ·

FAX: +1-800-824-3005 · [www.leviton.com/canada](http://www.leviton.com/canada)

**Leviton S. de R.L. de C.V.**

Lago Tana 43, Mexico DF, Mexico CP 11290 · Tel.: (+52)55-5082-1040 · FAX: (+52)5386-

1797 · [www.leviton.com.mx](http://www.leviton.com.mx)

**Visit our Website at: [www.leviton.com](http://www.leviton.com)**

© 2018 Leviton Manufacturing Co., Inc. All Rights Reserved. Subject to change without notice.

**Leviton has a global presence.**

If you would like to know where your local Leviton office is located please go to:

[www.leviton.com/international/contacts/](http://www.leviton.com/international/contacts/)

