



1000 V



0253-03NH-INS

Insulated Nut-Holding Nut Drivers

- Meets the IEC 60900 and ASTM F1505 standards for insulated tools
- Nut-Holding, non-magnetic design – won't collect metal filings, works with stainless steel and brass
- Helps meet the requirements of OSHA 1910 331-335, NFPA 70E & CSA-Z462
- Dual layer insulation helps provide added safety and protection against electric shock
- Set includes:
 - 3/16" x 6" Insulated Nut Driver
 - 1/4" x 6" Insulated Nut Driver
 - 5/16" x 6" Insulated Nut Driver
 - 11/32" x 6" Insulated Nut Driver
 - 3/8" x 6" Insulated Nut Driver
 - 7/16" x 6" Insulated Nut Driver
 - 1/2" x 6" Insulated Nut Driver
 - Custom Tool Roll-Up Carrier

CAT. NO.	UPC NO.	DESCRIPTION
0253-03NH-INS	783310134732	Insulated Nut-Holding Nut Drivers, 7 Piece Kit
0253-17NH-INS	783310134800	Insulated Nut-Holding Nut Drivers, 1/2" x 6"
0253-12NH-INS	783310134756	Insulated Nut-Holding Nut Drivers, 1/4" x 6"
0253-14NH-INS	783310134770	Insulated Nut-Holding Nut Drivers, 11/32" x 6"
0253-11NH-INS	783310134749	Insulated Nut-Holding Nut Drivers, 3/16" x 6"
0253-15NH-INS	783310134787	Insulated Nut-Holding Nut Drivers, 3/8" x 6"
0253-13NH-INS	783310134763	Insulated Nut-Holding Nut Drivers, 5/16" x 6"
0253-16NH-INS	783310134794	Insulated Nut-Holding Nut Drivers, 7/16" x 6"

SPECIFICATIONS

	3/16"	1/4"	5/16"	11/32"	3/8"	7/16"	1/2"
Overall Length	10-1/4" (26.0 cm)	10-7/8" (27.6 cm)	10-7/8" (27.6 cm)				
Weight	0.33 lb (.15 kg)	0.33 lb (.15 kg)	0.36 lb (.16 kg)	0.37 lb (.17 kg)	0.37 lb (.17 kg)	0.46 lb (.21 kg)	0.50 lb (.23 kg)