

PRODUCT-DETAILS

A2A 250 TMF 200-2000 3p F F UL

A2A 250 TMF 200-2000 3p F F UL



General Information

Extended Product Type	A2A 250 TMF 200-2000 3p F F UL
Product ID	1SDA069792R1
EAN	8015644705428
Catalog Description	A2A 250 TMF 200-2000 3p F F UL
Long Description	C.BREAKER FORMULA A2A 250 UL/CS A FIXED THREE-POLE WITH FRONT TERMINALS AND THERMOMAGNETIC RELEASE TMF R 200-2000 A

Ordering

EAN	8015644705428
Minimum Order Quantity	1 piece
Customs Tariff Number	85362090

Dimensions

Product Net Width	105 mm
Product Net Height	150 mm
Product Net Depth / Length	60 mm
Product Net Weight	1.3 kg

Container Information

Package Level 1 Units	1 piece
Package Level 1 Width	162 mm
Package Level 1 Height	120 mm
Package Level 1 Depth / Length	155 mm
Package Level 1 Gross Weight	1.35 kg
Package Level 1 EAN	8015644705428

Technical UL/CSA

Interrupting Rating acc. to UL489	(240 V) 10 kA (250 V DC) 2 Poles in Series 10 kA
-----------------------------------	---

Additional Information

Number of Poles	3
Product Main Type	SACE FORMULA
Product Name	Moulded Case Circuit Breaker
Product Type	CB
Rated Current (I_n)	Main Circuit 200 A
Rated Impulse Withstand Voltage (U_{imp})	6 kV
Rated Insulation Voltage (U_i)	690 V
Rated Operational Voltage	240 V AC 250 V DC
Rated Uninterrupted Current (I_u)	250 A
Release	TMF
Release Type	TM
Short-Circuit Performance Level	A
Standards	UL
Sub-type	A2
Terminal Connection Type	Front
Version	F

Certificates and Declarations (Document Number)

Data Sheet, Technical Information	1SXU210022D0201
Declaration of Conformity - CE	9AKK106713A5518
Environmental Information	1SDL000183R0001
Instructions and Manuals	1SDH000718R0003

Classifications

ETIM 6	EC000228 - Power circuit-breaker for trafo/generator/installation prot.
ETIM 7	EC000228 - Power circuit-breaker for trafo/generator/installation protection
WEEE Category	5. Small Equipment (No External Dimension More Than 50 cm)

Categories

Low Voltage Products and Systems → Circuit Breakers → Moulded Case Circuit Breakers → Formula DSA

